



## Basic features

Approval/Conformity	CE cULus EAC WEEE
Basic standard	IEC 60947-5-2
Principle of operation	Inductive sensor

## Display/Operation

Function indicator	yes
Power indicator	no

## Electrical connection

Connection	M12x1-Male, 4-pin, A-coded
Polarity reversal protected	yes
Protection against device mix-ups	yes
Short-circuit protection	yes

## Electrical data

Load capacitance max. at $U_e$	1 $\mu$ F
Min. operating current $I_m$	0 mA
No-load current $I_o$ max., damped	12 mA
No-load current $I_o$ max., undamped	10 mA
Operating voltage $U_b$	10...30 VDC
Output resistance $R_a$	47.0 k $\Omega$ m
Rated insulation voltage $U_i$	75 V DC
Rated operating current $I_e$	200 mA
Rated operating voltage $U_e$ DC	24 V
Rated short circuit current	100 A
Ready delay $t_v$ max.	50 ms
Residual current $I_r$ max.	100 $\mu$ A
Ripple max. (% of $U_e$ )	20 %
Switching frequency	500 Hz
Utilization category	DC -13
Voltage drop static max.	2 V

## Environmental conditions

Ambient temperature	-25...70 °C
Contamination scale	3
EN 60068-2-27, Shock	Half-sinus, 30 $g_n$ , 11 ms
EN 60068-2-6, Vibration	55 Hz, amplitude 1 mm, 3x30 min
IP rating	IP67

## Functional safety

MTTF (40 °C)	945 a
--------------	-------

## Interface

Switching output	PNP normally open (NO)
------------------	------------------------

## Material

Housing material	Brass, Chrome-plated
Material sensing surface	PBT

## Mechanical data

Dimension	Ø 8 x 66 mm
Installation	non-flush
Mounting length	42.00 mm
Size	M8x1
Tightening torque	4 Nm

## Range/Distance

Assured operating distance Sa	4.8 mm
Hysteresis H max. (% of Sr)	15.0 %
Rated operating distance Sn	6 mm
Real switching distance sr	6 mm
Repeat accuracy max. (% of Sr)	5.0 %
Temperature drift max. (% of Sr)	10 %
Tolerance Sr	±10 %

## Remarks

The sensor is functional again after the overload has been eliminated.

Working frequency f oscillator: 320 kHz. In the range of ±15% of the working frequency EMC incompatibilities may occur.

With connector, e.g. BCC M425-.. total length is = switch length +19 mm.

For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

## Connector Drawings



## Wiring Diagrams (Schematic)

